


Four Row Cylindrical Roller Bearing

VISTA®
Bearing



Bærer NEJ.		Grænsemål [mm]					Grundlæggende belastningsvurderinger (kN)		Begrænsningshastighed (r / min)		Vægt (kg)
New	Old	d	D	B	R2smin	Fw(Ew)	Cr	Cor	Old_spec	Betegnelser	
FC202780	-	100	135	80	1.5	110	200	510	3400	4000	3
FC202880	-	100	138	80	1.5	110	260	600	3400	4000	3.7
FC202870	672820K	100	140	70	1.5	111	190	410	3400	4000	3.5
FC2028104	672820	100	140	104	1.5	111	290	700	3400	4000	5.1
FC202970	672720	100	145	70	1.5	113	220	460	3400	4000	4.1
FC2030106		100	150	106	1.5	113	350	740	3400	4000	6.8
FC223080	-	110	150	80	1.5	122	240	600	3100	3800	4.4
FC223490	672722K	110	170	90	2	127	360	750	2800	2600	7.9
FC2234120	672722	110	170	120	2	127	360	750	2800	3600	10.6
FC243692	-	120	180	92	2	137	375	820	2600	3400	8.7
FC2436105	672724	120	180	105	2	136	430	920	2600	3400	9.8
FC2436120	-	120	180	120	2	136	480	1060	2600	3400	11.2
FC2640104	-	130	200	104	2	150	480	1000	2400	3000	12.5
-	672726	130	200	125	3	149	530	1140	2400	3000	15
FC2838119	-	140	190	119	2	154	470	1250	2400	3000	9.5
FC2842100	-	140	210	100	2	158	500	1100	2200	2800	12.8
FC2842106	-	140	210	106	2	158	500	1100	2200	2800	13.6
FC2842125	-	140	210	125	2	158	620	1360	2200	2800	15.87
FC2842155	-	140	210	155	2	158	760	1770	2200	2800	19.6
FC2942155	-	145	210	155	2	166	720	1560	2200	2800	17.5
FC2945156	-	145	225	156	2	169	800	1940	2000	2600	24.4
FC3042120	-	150	210	120	2	166	600	1500	2200	2800	12.5
FCD3042120	-	150	210	120	2	166	600	1500	2200	2800	12.5
FC3044120	-	150	220	120	2	167	630	1360	2100	2700	15

Four Row Cylindrical Roller Bearing

SFC3045120	-	150	225	120	2	169	790	1560	2000	2600	17.3
FC3045120	672730K	150	225	120	2	169	725	1590	2000	2600	17.5
FC3045150	-	150	225	150	2	169	780	1750	2000	2600	20
FC3046156	672760	150	230	156	2	174	815	1660	2000	2600	23.5
SFC3046156	-	150	230	156	2	174	815	1900	2000	2600	23.5
FC3245168	-	160	225	168	2	183	950	2300	2000	2600	-