


Four Row Tapered Roller Bearing

VISTA®
Bearing



Lejer nr.	Gammelt nr.	Grænsemål [mm]						Grundlæggende belastningsvurderinger (kN)		Masse
		d	D	T	B	Rsmin	rs min	Dynamisk (Cr)	Statisk (Cor)	Kg
7740	77740	200	310	200	200	3	2.5	1970	4250	55.6
-	2077140	200	310	275	275	3	2.5	1230	4200	75.1
77741	77741	205	320	205	205	4	3	1060	2850	55.4
2077144E	2077144E	220	340	305	305	4	3	2457	5974	100.8
2077148	2077148	240	360	310	310	4	3	3300	7210	90.5
330782A	-	241.478	349.148	228.6	228.6	1.5	3.3	1732	4387	70.4
380650	3-703	250	385	255	255	3	3	2127	4948	107.8
77750Y	77750Y	250	460	270	270	4	4	3040	5726	196
382952	2077952	260	360	265	265	3	3	1990	5770	80
381052X2/HC	77752	260	400	255	255	5	5	2109	4957	123
382052	-	260	400	345	345	5	4	2850	7700	161
77752	77752	260	440	300	300	2	5	2715	5968	164
330822B	-	266.7	355.6	228.6	230.188	1.5	3.3	1780	5340	62.8
-	77756	280	420	250	250	5	5	1540	5300	119
381156	1077756	280	460	324	324	5	4	3780	8560	215.7
-	2077160	300	460	390	390	5	4	3850	10200	222
-	2077164	320	480	380	380	5	4	3000	11500	252
-	2077968	340	460	310	310	4	4	2200	9300	147
381068	-	340	520	325	325	5	4	3200	8200	247
-	77872	360	480	375	375	4	4	2550	1800	197
107772	1077772	360	600	420	420	4.7	4.7	3950	13500	388
-	77776	380	550	350	30	5	5	3800	10000	271

Four Row Tapered Roller Bearing

-	3077776	380	620	388	388	6	6	3450	11600	443
381176	1077776	380	620	420	420	5	4	5050	12600	485
-	77779	395	545	288.7	268.7	10	10	2361	6558	191
-	77880	400	540	280	280	3.7	7.5	2450	6500	187
380680	-	400	540	400	400	5	5	6350	13300	262
381080	-	400	600	356	356	5	4	3400	12400	345
380684	-	420	560	437	437	5	5	7180	16300	298
381184	1077784	420	700	480	480	6	5	9550	18200	755