


Thrust Angular Contact Ball Bearing

VISTA®
Bearing



Lejer nr.	Gammelt nr.	Grænsemål [mm]							Grundlæggende belastningsvurderinger (kN)		Begrænsningshastighed (o / min)		Masse (kg)
		d	d1min	D	D1max	H	a	rs min	Dynamisk (Cr)	Statisk (Cor)	Old_spec	Betegnelser	
569184	9168184	420	430	500	490	48	60°	2	260	1440	830	1100	15.9
567284	7168284	420	462	580	538	73	45°	5	330	2010	700	980	51
569188	9168188	440	458	540	522	60	45°	2.1	380	1980	660	950	25.5
5691/500	91681/500	500	530	600	570	60	60°	2.1	322	1956	660	950	25.3
5613/520	1689/520	520	554	620	586	60	60°	2.1	409	2247	400	570	26.9
5692/530	91682/530	530	590	710	650	109	60°	5	738	4162	350	500	90.3
5617/560	1687/560	560	620	740	680	89	45°	6	805	3432	400	570	77
5991/600	91681/600	600	635	675	710	67	60°	3	504	3010	510	710	37.6
5617/610	1687/610	610	700	790	735	89	45°	4.5	840	3648	380	540	86
5617/620	1687/620	620	665	780	735	102	45°	3.5	776	3588	340	490	95.2
5692/620	91682/620	620	680	800	740	109	60°	5	902	4720	260	370	103.1
5617/650	1687/650	650	690	880	840	140	60°	6	1100	7280	260	370	200
5692/670	91682/670	670	740	900	830	140	45°	6	1260	6085	250	360	206
5691/750	91681/750	750	780	900	870	90	60°	4	587	4620	340	480	94.4
5611/800	1681/800	800	850	950	900	120	60°	4	866	6414	200	240	133.6
5692/800	91682/800	800	890	1060	970	155	60°	7.5	1134	9394	180	180	301.9
5617/810	1687/810	810	880	1030	960	110	45°	7.5	780	4080	280	400	176
5691/950	91682/950	950	1040	1250	1160	180	45°	7.5	1500	9168	120	170	432
5691/1000	91681/1000	100	1040	1180	1140	109	45°	5	1076	6516	250	360	177
5691/1120	91681/1120	1120	1170	1320	1270	122	60°	5	1020	10270	180	260	241
5617/1600	1687/1600	1600	1600	1760	1760	90	60°	6	685	8055	210	300	248
5617/1860	1687/1860	1860	1900	2100	2060	140	60°	4.5	1275	19370	92	130	577