



Betegnelse	Hovedmål (mm)					Grundlæggende belastningsvurderinger (KN)		Begrænset hastighed (o / min)		Vægt (kg)
	d	D	B	rs min	rs1min	Dynamisk (Cr)	Statisk (Cor)	Fedt	Olie	
NU2230E	150	270	73	3	3	660	980	2000	2400	19.7
NU2230	150	270	73	3	3	500	710	2200	2600	16.3
NU2228E	140	250	68	3	3	575	835	2100	2500	15.8
NU2228	140	250	68	3	3	445	635	2400	2800	12.9
NU2226E	130	230	64	3	3	530	735	2300	2700	11.8
NU2226	130	230	64	3	3	380	530	2600	3100	10.2
NU2224E	120	215	58	2.1	2.1	450	620	2600	3000	9.18
NU2224	120	215	58	2.1	2.1	350	460	2900	3400	8.19
NU2222E	110	200	53	2.1	2.1	385	515	2800	3300	7.4
NU2222	110	200	53	2.1	2.1	320	415	3100	3700	6.56
NU2220E	100	180	46	2.1	2.1	335	445	3100	3600	5.01
NU2220	100	180	46	2.1	2.1	258	340	3500	4100	4.57
NU2219E	95	170	43	2.1	2.1	286	370	3300	3800	4.14
NU2219	95	170	43	2.1	2.1	230	298	3600	4300	3.79
NU2218E	90	160	40	2	2	242	315	3500	4100	3.33
NU2218	90	160	40	2	2	197	248	3900	4600	3.1
NU2217E	85	150	36	2	2	217	279	3700	4300	2.68
NU2217	85	150	36	2	2	170	218	4100	4800	2.44

NU2200 Series

NU2216E	80	140	33	2	2	186	243	3900	4600	2.12
NU2216	80	140	33	2	2	147	186	4400	5100	1.93
NU2215E	75	130	31	1.5	1.5	162	207	4200	4900	1.79
NU2215	75	130	31	1.5	1.5	130	162	4700	5500	1.55
NU2214E	70	125	31	1.5	1.5	156	194	4500	5200	1.7
NU2214	70	125	31	1.5	1.5	119	151	5000	5900	1.47
NU2213E	65	120	31	1.5	1.5	149	181	4800	5600	1.6
NU2213	65	120	31	1.5	1.5	120	149	5400	6300	1.4
NU2212E	60	110	28	1.5	1.5	131	157	5200	6100	1.21
NU2212	60	110	28	1.5	1.5	96	116	5800	6800	1.06
NU2211E	55	100	25	1.5	1.1	97	114	5600	6600	0.968
NU2211	55	100	25	1.5	1.1	75.5	87	6300	7400	0.773