



Betegnelse	Hovedmål (mm)					Grundlæggende belastningsvurderinger (KN)		Begrænset hastighed (o / min)		Vægt (kg)
	d	D	B	rs min	rs1min	Dynamisk (Cr)	Statisk (Cor)	Fedt	Olie	
NJ230E	150	270	45	3	3	450	595	2200	2600	11
NJ230	150	270	45	3	3	345	435	2500	2900	9.92
NJ228E	140	250	42	3	3	395	515	2400	2800	8.73
NJ228	140	250	42	3	3	310	400	2700	3100	7.88
NJ226E	130	230	40	3	3	365	455	2600	3100	6.9
NJ226	130	230	40	3	3	270	340	2900	3400	6.3
NJ222	110	200	38	2.1	2.1	240	290	3400	4000	4.63
NJ224	120	215	40	2.1	2.1	260	320	3200	3700	5.57
NJ221	105	190	36	2.1	2.1	201	241	3600	4300	3.95
NJ220	100	180	34	2.1	2.1	183	217	3800	4500	3.33
NJ219E	95	170	32	2.1	2.1	220	265	3600	4300	3.02
NJ219	95	170	32	2.1	2.1	166	195	4000	4700	2.78
NJ218E	90	160	30	2	2	182	217	3900	4600	2.44
NJ218	90	160	30	2	2	152	178	4300	5000	2.3
NJ217E	85	150	28	2	2	167	199	4100	4800	2.11
NJ217	85	150	28	2	2	120	140	4500	5300	1.87
NJ216	80	140	26	2	2	106	122	4800	5700	1.5
NJ216E	80	140	26	2	2	139	167	4400	5100	1.67

NJ200 Series

NJ215E	75	130	25	1.5	1.5	130	156	4700	5500	1.41
NJ215	75	130	25	1.5	1.5	96.5	111	5100	6000	1.23
NJ214E	70	125	24	1.5	1.5	119	137	5000	5900	1.3
NJ214	70	125	24	1.5	1.5	83.5	95	5500	6500	1.12
NJ213E	65	120	23	1.5	1.5	108	119	5400	6300	1.21
NJ213	65	120	23	1.5	1.5	84	94.5	5900	7000	1.02
NJ212E	60	110	22	1.5	1.5	97.5	107	5800	6800	0.923
NJ212	60	110	22	1.5	1.5	68.5	75	6400	7600	0.818
NJ211E	55	100	21	1.5	1.1	82.5	93	6300	7400	0.718
NJ210E	50	90	20	1.1	1.1	66	72	6900	8100	0.54
NJ211	55	100	21	1.5	1.1	58	62.5	6900	8200	0.638
NJ210	50	90	20	1.1	1.1	48	51	7600	9000	0.47